

## 22mm (7/8") ASSEMBLED OIL TIGHT ILLUMINATED SELECTOR SWITCHES

Assembled Unit = Insert + Knob + Operator + Contact Block + Bulb

### 2-POSITION ILLUMINATED SELECTOR SWITCHES

| STYLE | MOUNTING POSITION | CONTACTS | OPERATOR POSITION |   | CATALOG NO. Maintained   | LIST PRICE | CATALOG NO. Spring Return from Right | LIST PRICE |
|-------|-------------------|----------|-------------------|---|--------------------------|------------|--------------------------------------|------------|
|       |                   |          | L                 | R |                          |            |                                      |            |
| Knob  | 1                 | 1 N/O    | O                 | X | KLS-2BRS (1,2) 2 (3) 10S | \$25.50    | KLS-2BRS (1,2) 2R (3) 10S            | \$25.50    |
|       | 2                 |          |                   |   |                          |            |                                      |            |
| Knob  | 1                 | 1 N/C    | X                 | O | KLS-2BRS (1,2) 2 (3) 01S | \$25.50    | KLS-2BRS (1,2) 2R (3) 01S            | \$25.50    |
|       | 2                 |          |                   |   |                          |            |                                      |            |
| Knob  | 1                 | 1 N/O    | X                 | O | KLS-2BRS (1,2) 2 (3) 11S | \$29.50    | KLS-2BRS (1,2) 2R (3) 11S            | \$29.50    |
|       | 2                 | 1 N/C    | O                 | X |                          |            |                                      |            |

### 3-POSITION ILLUMINATED SELECTOR SWITCHES

| STYLE | MOUNTING POSITION | CONTACTS | OPERATOR POSITION |   |   | CATALOG NO. Maintained    | LIST PRICE | CATALOG NO. Spring Return from Right | LIST PRICE |
|-------|-------------------|----------|-------------------|---|---|---------------------------|------------|--------------------------------------|------------|
|       |                   |          | L                 | C | R |                           |            |                                      |            |
| Knob  | 1                 | 2 N/O    | X                 | O | O | KLS-2BRS (1,2) 3 (3) 20S  | \$29.50    | KLS-2BRS (1,2) 3R (3) 20S            | \$29.50    |
|       | 2                 |          | O                 | O | X |                           |            |                                      |            |
| Knob  | 1                 | 2 N/C    | O                 | X | X | KLS-2BRS (1,2) 3 (3) 02S  | \$29.50    | KLS-2BRS (1,2) 3R (3) 02S            | \$29.50    |
|       | 2                 |          | X                 | X | O |                           |            |                                      |            |
| Knob  | 1                 | 2 N/O    | X                 | O | O | KLS-2BRS (1,2) 3 (3) 22S  | \$37.50    | KLS-2BRS (1,2) 3R (3) 22S            | \$37.50    |
|       | 2                 | 2 N/C    | O                 | O | X |                           |            |                                      |            |
|       | 3                 |          | O                 | X | X |                           |            |                                      |            |
|       | 4                 |          | X                 | X | O |                           |            |                                      |            |
| Knob  | 1                 | 2 N/O    | X                 | O | O | KLS-2BRS (1,2) 3L (3) 20S | \$29.50    | KLS-2BRS (1,2) 3LR (3) 20S           | \$29.50    |
|       | 2                 |          | O                 | O | X |                           |            |                                      |            |
| Knob  | 1                 | 2 N/C    | O                 | X | X | KLS-2BRS (1,2) 3L (3) 02S | \$29.50    | KLS-2BRS (1,2) 3LR (3) 02S           | \$29.50    |
|       | 2                 |          | X                 | X | O |                           |            |                                      |            |
| Knob  | 1                 | 2 N/O    | X                 | O | O | KLS-2BRS (1,2) 3L (3) 22S | \$37.50    | KLS-2BRS (1,2) 3LR (3) 22S           | \$37.50    |
|       | 2                 | 2 N/C    | O                 | O | X |                           |            |                                      |            |
|       | 3                 |          | O                 | X | X |                           |            |                                      |            |
|       | 4                 |          | X                 | X | O |                           |            |                                      |            |

### ORDER INFORMATION

|          |  |                    |  |                       |  |   |   |  |   |               |               |          |          |            |
|----------|--|--------------------|--|-----------------------|--|---|---|--|---|---------------|---------------|----------|----------|------------|
| <b>K</b> | <b>S</b>   | <b>2</b>           | <b>B</b>                                 | <b>R</b>              | <b>S</b>   | <b>(1)</b>  | <b>(2)</b>  | <b>2</b>   | <b>-</b>  | <b>(3)</b>    | <b>10</b>     | <b>S</b> | <b>-</b> | <b>LED</b> |
| Company  | Item   | Mounting Hole Size | Guard Color & Material                   | Guard Type            | Lever Type                                       | Lever Color   | Indicator Color   | Voltage  | Contact Block   | Terminal Type | Bulb Type     |          |          |            |
| K: KACON | S: Selector Switch<br>LS: Lighted Lever<br>LI: Lighted Indicator | 2: 22mm<br>3: 30mm | B: Black Standard<br>A: Aluminum (Round) | R: Round<br>W: Square | S: Knob<br>L: Lever<br>H: Handle (Selector Only) | B: Black<br>R: Red<br>G: Green<br>Y: Yellow<br>W: White | W: White<br>R: Red<br>Y: Yellow<br>G: Green<br>L: Lighted Lever | A1: AC100 ~ 115V<br>A3: AC220 ~ 240V<br>D1: DC100 ~ 125V<br>D2: DC24V<br>D3: DC12V<br>D4: DC6.3V | 10: 1A<br>01: 1B<br>11: 1A1B<br>20: 2A<br>:<br>44: 4A4B | S: Screw      | LED: LED Bulb |          |          |            |

(1) Lever Color Code: B = Black, R = Red, G = Green, Y = Yellow, W = White.

(2) Indicator Color Code: W = White, R = Red, G = Green, Y = Yellow.

(3) Voltage Code: A1 = 120VAC, A2 = 208VAC, A3 = 220VAC (Transformer), D1 = 100/125VDC, D2 = 24VAC/DC, D3 = 12VAC/DC, D4 = 6.3VAC/DC (Direct Supply)

Note: Contact your nearest sales office for other cam arrangements.

| Function  |  |
|---|--|
| 2: 2-Position                                   |  |
| 3: 3-Position                                   |  |
| 2R: 2-Position Spring Return from Right         |  |
| 3R: 3-Position Spring Return from Right         |  |
| 3L: 3-Position Spring Return from Left          |  |
| 3LR: 3-Position Spring Return from Left & Right |  |