



80MM LED TOWER LIGHT

ST80L

MODEL TYPES::

- ST80L** ➤ Continuous LED tower light
- ST80LF** ➤ Continuous and flashing LED tower light
- ST80LB** ➤ Continuous LED tower light with buzzer (85dB)
- ST80LZ** ➤ Continuous and flashing LED tower light with buzzer (85dB)

ST80L FEATURES ::

- Pre-wired pre-assembled with threaded poles and nut
- Long life, high intensity LED technology
- Special light refractor spreads light to fill lens
- Vibration resistant
- Stackable sections allow changing of color sequence
- Flashes: 60-80/min
- Optional audible (85dB) alarm
- IP23 rated
- Standard color sequence: 1: red 2: red-green 3: red-amber-green 4: red-amber-green-blue 5: red-amber-green-blue-white



ORDERING INFORMATION ::

MODEL TYPE:: ST80L, ST80LF, ST80LB, ST80LZ

COLORS:: red, amber, green, blue, white

VOLTAGE:: 12, 24, 110, 220

EXAMPLE:: ST80LF-110-5
[continuous and flashing, 5 lights, 110V, red amber green blue white]

VOLTAGE	CURRENT (TS/TL)	FLASH/MIN
12V DC	0.110A	60-80/min
24V DC	0.110A	60-80/min
110V AC	0.080A	60-80/min
220V AC	0.040A	60-80/min

