

MODEL TYPES ::

- MX-LED 110/230V** > Mains MX-LED Beacon
- MX-LED MV** > Multivoltage MX-LED Beacon

FEATURES ::

- > A bright LED beacon with low power consumption
- > Multivoltage 10-100Vdc, and mains 110Vac and 230Vac versions
- > Unique patented design maximizes light output
- > Clear lens with coloured LEDs
- > Low power consumption
- > 3 year guarantee
- > Weatherproof to IP65
- > CE – certified to EMC directive 2004/108/EC
- > Complies with low voltage directive 2006/95/EC
- > High voltage transient and polarity reversal protected
- > Operating temperature: -20° C to +55° C



ACCESSORIES + OPTIONS ::

- > Sounder plinth, fixes to base of beacon, FX29 (multivoltage version only)



MATERIALS ::

- > Polycarbonate lens and base
- > ROHS compliant






ORDERING ::

MX-LED 110/230V A = Amber Beacon
 MX-LED 110/230V R = Red Beacon

MX-LED MV A = Amber Beacon
 MX-LED MV R = Red Beacon

INFORMATION ::

- > Mains 110/230V - 25mA @ 110Vac
 - 15mA @ 230Vac
- > Multivoltage MV - 230mA @ 12Vdc
 - 110mA @ 24Vdc
 - 60mA @ 50Vac
 - 40mA @ 100Vac

					
Mains 110/230V	Amber>15cd Red>25cd	65 flashes/min 6 bursts/flash	85–265Vac	IP65	310gms
Multivoltage MV			10–100Vdc		