

Alarm Sounder & Xenon Strobe

UL Cl 1 Div 1, 125dB, 5 Joule


SIGNAWORKS
www.signaworks.com

MODEL TYPES

D1XC2X05F > Alarm Sounder & Xenon Strobe

FEATURES

- > Automatic synchronization on multi-beacon & sounder systems.
- > User selectable strobe flash rates
- > Ratchet adjustable stainless steel 'U' bracket.
- > High output alarm horn, up to 1250dB(A)
- > Xenon strobe - private mode fire alarm use
- > Alarm horn - public mode fire alarm use
- > 4 remotely selectable alarm stages/channels
- > Positive or negative line stage/channel switching
- > Choice of 64 alarm tone frequencies
- > Compact form factor
- > Robust corrosion proof aluminum enclosure
- > Stainless steel fixings
- > Triple cable entries
- > Duplicate cable terminations
- > UL Approval



ORDERING INFORMATION

Product Code (0)	> D1XC2X05F
Horn (1)	> R (omni-direction radial buzzer)
Voltage (2)	> DC024 (20-28V dc) , AC115 (115-120V ac) , AC230 (220-240V ac)
Cable Type (3)	> A (1x1/2'NPT & 2 x M20 x 1.5mm), B (1x1/2'NPT & 2 x 1/2'NPT), C (1x1/2'NPT & 2 x 3/4'NPT)
Adapter Mat. (4)	> B (Brass), N (Nickel Plated), S (Stainless Steel)
Bracket Mat. (5)	> 1 (A2 304 Stainless Steel), 2 (A4 316 Stainless Steel)
Product Version (6)	> A1 (Gas env. Class I) , D1 (Dust env. Class II)
Enclosure Color (7)	> G (Grey), R (Red)
Lens Color (8)	> R (Red), A (Amber), G (Green), B (Blue), C (Clear), Y (Yellow), M (Magenta)
Example	> ordering - (0) (1) (2) (3) (4) (5) (6) (7) (8) D1XC2X05F-R-AC230-A-B-1-A1-G-R

DIMENSIONS



