

Pilot Light AC



MODEL TYPES


- KL-2BRR > Round Flat Lens
- KL-2BRD > Round Dome Lens
- KL-2BSS > Square Flat Lens
- KL-2BDRDR > Arrow Lens

TYPES


Round Flat Lens



Square Flat Lens



Round Dome Lens



Arrow Lens



ORDERING INFORMATION

Style	Voltage		Suitable Lamp	Catalog No.
	Primary	Secondary		
Round Flat Lens	120V AC	5.5V AC	BA9S-T1-6.3V 1W	KL-2BRR (1)-A1S
	220V AC			KL-2BRR (1)-A3S
Round Dome Lens	120V AC			KL-2BRD (1)-A1S
	220V AC			KL-2BRD (1)-A3S
Square Flat Lens	120V AC			KL-2BSS (1)-A1S
	220V AC			KL-2BSS (1)-A3S
Arrow Lens	120V AC			KL-2BDRDR (1)-A1S
	220V AC			KL-2BDRDR (1)-A3S

K	L	-	2	B	R	R	(1)	-	(2)	S	-	LED
Company	Item		Mounting Hole	Guard Color	Guard Type	Lens Type	Lens Color		Voltage	Terminal Type		Bulb
K: KACON	L: Pilot Lamp		Size	& Material	R: Round	R: Round	R: Red	A1: AC100/115V	S: Screw			LED: LED Bulb
			2: 22 mm	B: Black	S: Square	S: Square	G: Green	A3: AC220/240V				
			3: 30 mm	(Plastic)	RF: Round	D: Dome	Y: Yellow	D1: DC100 - 125V				
				A: Aluminum	Full Guard	DR: Direction	B: Blue	D2: DC24V				
				(Round)	Indicator	Indicator	W: White	D3: DC12V				
								D4: DC6.3V				

(1) Lens Color Code: R = Red, G = Green, Y = Yellow, B = Blue, W = White.

(2) Voltage Code: A1 = 120VAC, A3 = 220VAC, D1 = 100/125VDC, D2 = 24VAC/DC, D3 = 12VAC/DC, D4 = 6.3V AC/DC.