

LED Area Work Light



MODEL TYPES

- QWL150 > LED Indoor Working Lights - 150mm
- QWL250 > LED Indoor Working Lights - 250mm
- QML150 > LED Indoor Working Lights w/ Frosted Lens - 150mm
- QML250 > LED Indoor Working Lights w/ Frosted Lens - 250mm

EXTRAS

H > High Output Light (QWHL250-QBK01)

MOUNTING

- QBK01 > 3 Hole triangular Mounting
- QBK02 > 4 Hole square Mounting + hole for wire
- QBK03 > Swivel Mounting

FEATURES

- > High luminance SMD LED offers a strong level of illumination in a large space
- > Glare shield tempered glass is employed for improving anti-dazzle and shock resistance
- > Die casting aluminum structure is resistant to vibration, impact and heat
- > Oil resistant cable is applied for machine tools exposed to cutting oil
- > Compact size and possible to be installed in a limited space
- > IP 67 rating is suitable for using in the environment with oil, dust and metal chips
- > Material : Body-AL, Lens-Tempered Glass
- > Lux : 450 Lux at 1m
- > Protection Class : IP67

ORDERING INFORMATION

Ordering Examples	> (Q - W/M - *H - L - 150/250 - *QBK0(1,2,3))		
QWSL150	DC24V / 0.6A	DC: 450 Lux at 1m	
QWSL250	DC24V / 0.245A	DC: 1800 Lux at 1m	
QML150	DC24V / 0.58A	DC: 520 Lux at 1m	
QML250	DC24V / 1.35A	DC: 1,047 Lux at 1m	

*H: High Output Light
W/M: W - Clear Glass, M - White/Frosted Glass
150/250: 150mm, 250mm Length

*QBK0(1,2,3): QBK01 - 3 hole mounting bracket,
QBK02 - 4 hole + 1 for wire mounting bracket,
QBK03 - Swivel Mounting Bracket

* - Optional Features

DIMENSIONS

